

BFM® Bulk Bag Loader



Filling bulk bags – fast, leak-proof, safe!

Tool-free connection to the filling station with proven BFM® clamping ring system

- Expansion sleeve function guarantees perfect sealing of the connection point to the inlet spout of the big bag
- Suitable for most big bags with filling spout available on the market
- Proven Seeflex E material with all necessary approvals for use in all industries



Here's how:

- Pull the inlet spout of the big bag over the BFM® inflation collar
- Start compressed air (e.g. via foot pedal) until the spout is firmly in place – ATTENTION: max. pressure 400 mbar (caution: volume flow for safety valve lower than filling valve!)
- Start dust-tight filling; venting to be provided by customer
- Release compressed air, close inlet spout – done!

Available Sizes (standard length for all diameters 330 mm):

Diameter	Expands to fit bag neck sizes	Diameter	Expands to fit bag neck sizes
Ø 150 mm	Ø 160 – 200 mm	Ø 350 mm	Ø 370 – 460 mm
Ø 200 mm	Ø 220 – 260 mm	Ø 400 mm	Ø 420 – 540 mm
Ø 250 mm	Ø 270 – 340 mm	Ø 450 mm	Ø 470 – 590 mm
Ø 300 mm	Ø 320 – 395 mm		

This document does not imply any legally binding assurance concerning specific properties of the BFM® fittings or the suitability for a particular application. The responsibility of complying with any governing laws and regulations relevant to the use of BFM® fittings is the obligation of the user. Subject to technical changes without prior notice. BFM® is a registered trademark of BFM Global Ltd.

Walter Gerätebau GmbH / Neue Heimat 16 / 74343 Sachsenheim-Ochsenbach
T +49 7046 980-0 / info@walter-cleaningsystems.de / www.walter-cleaningsystems.de