

Walter Safe

Access control for your BFM® Fitting



- Safe access control: can only be opened with a special key.
- Prepared for optional use with electronic sensor (inductive).
- Quick and easy installation: no welding, no drilling required.
- Visual control of the BFM® connector behind the grid still possible.
- For connector diameters 150–300 mm.
- For installation heights between 80 – 190 mm (depending on the individual installation situation and with only slight mechanical modifications).
- Made from stainless steel (1.4571), easy to clean.

Installation: The Walter safe is simply clamped onto the top BFM® spigot with two screws only. Afterwards the grid door is fit into the hinges with two bolts – ready! Any BFM® Fitting already installed can be retrofitted easily without disruption of production.

Not recommended for heavy movement and / or offset connectors.

This document does not imply any legally binding assurance concerning specific properties of the BFM® fittings or the suitability for a particular application. The responsibility of complying with any governing laws and regulations relevant to the use of BFM® fittings is the obligation of the user. Subject to technical changes without prior notice. BFM® is a registered trademark of BFM Global Ltd.

Walter Gerätebau GmbH / Neue Heimat 16 / 74343 Sachsenheim-Ochsenbach
T +49 7046 980-0 / info@walter-cleaningsystems.de / www.walter-cleaningsystems.de